



CERTIFICATE OF CONFORMITY

This is to certify that
DuPont™
FlexWrap™ NF



Product Description

DuPont™ FlexWrap™ NF is a stretchable & flexible wrap made up of 3 components:

1. DuPont™ Tyvek® top sheet providing a water tight layer.
2. 100% Butyl Rubber as an adhesive layer
3. A paper release liner.

Product Purpose or Use

To be used to create a watertight adhesion to all Tyvek® breather membranes around non-straight penetrations & corners of all rough openings such as: dormers, window & door sills, chimney breasts, pipe penetrations and any custom shapes.

Certificate Holder

DuPont™ Australia Ltd

ABN: 59 000 716 469
Level 3,7 Eden Park Drive
Macquarie Park NSW
Australia 2113
Ph: 02 9923 6148
W: www.dupont.com.au



Certification Body

CertMark International Pty Ltd

T/A CertMark New Zealand
ABN: 80 111 217 568
JAS-ANZ Accreditation No. Z4450210AK
PO Box 321 Tuakau 2121
www.CertMark.org

Complies with the New Zealand Building Code:

1. NZBC Clause B2 Durability: Performance B2.3.1 (b) & B2.3.2.
2. NZBC Clause E2 External Moisture: Performance E2.3.2.
3. NZBC Clause F2 Hazardous Building Materials: Performance F2.3.1.

Subject to the following Conditions & Limitations:

- a. Ensure all surfaces to which DuPont™ FlexWrap™ NF is applied are free from dirt, moisture, ice, grease and other materials which could reduce the adhesion.
- b. DuPont™ FlexWrap™ NF is to be installed when dry and when the roll temperature is warmer than -4°C/25°F.
- c. When applying DuPont™ FlexWrap™ NF to LOSP treated timber, ensure the solvent has been allowed to flash off prior to installing the product. It is suggested that a minimum of one (1) week is allowed for.
- d. DuPont™ FlexWrap™ NF when used, installed and maintained in accordance with the requirements outlined in DuPont™ DuPont Flashing Installation Guidelines April, 2015—New Zealand & Australia meets the requirements of Acceptable Solution E2/AS1 Amendment 6, Clause 9.1.5 (b) (i).
- e. After completion of the installation DuPont™ FlexWrap™ NF has to be covered within 4 months with the appropriate building materials.
- f. This certification relates only the clauses of the NZBC as contained herein. Consequently the following mandatory clauses are excluded from the certification: B1 Structure, C1 Fire & E1 Surface water these clauses are outside the scope of this Certificate. The need for compliance with the requirements of excluded clause in the use of the subject product are to be determined by the regulatory authority (building certifier or building surveyor).
- g. This certification relates only to the product that is described above, and has to be read, considered and used as a whole document — it may be considered misleading and will be incomplete to be selective.
- h. For further information contact the certificate holder.

John Thorpe
CertMark International Pty Ltd

27/04/2015

Date of Issue

CMA-CM40141

Certificate Number

- This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz
- This certificate may only be reproduced in its entirety.

