

Vapastop® Tape AF

Aluminium Foil Tape

Application

Vapastop® Tape AF is an aluminium tape with synthetic, high tack, high shear, pressure sensitive adhesive. It is an architectural tape that is not suitable for use where tape strength is required. However, its foil facing creates an attractive finish to compliment foil faced underlays as well as assisting in the creation of a vapour barrier.


It is suitable for use in the following applications:

- Vapour barriers
- Foil faced architectural linings

Features and Benefits

- Pure Aluminium Foil – Provides an effective vapour barrier
- Highly Reflective – Matches aluminium vapour barriers to provide an equivalent finish

Product Description



Technical Data

Backing Material	30 Micron aluminium foil
Adhesive Type	Synthetic rubber/resin
Tensile Strength	42 N/25mm
Adhesion To Steel	25 N/25mm
Elongation At Break	5%
Total Thickness Without Liner	75 Microns
Recommended Service Temperature	5 to 65°C

Installation

General

- For best adhesion ensure tapes are warmed to over 10°C before application (e.g. tape should not be cold to the touch)
- Prepare the surface to be joined by ensuring it is free of any excess moisture or debris
- Use the correct width tape to ensure an effective join. The wider tapes provide greater adhesion and ease of application over narrower tapes.
- Ensure the tape is centrally positioned over the join for the most effective and aesthetic finish
- Once tape is applied rub firmly to ensure firm adhesion (the use of a squeegee is recommended)

Durability

When used, installed and maintained in accordance with the requirements outlined in this datasheet, Vapastop® Tape AF will meet or contribute to meeting the following provisions of the NZBC:
 NZBC Clause B2: Durability Meets the requirements of NZBC B2.3.1 a) 50 years and NZBC B2.3.1 b) 15 years

Specification Notes

Product required: Vapastop® Tape AF Aluminium Foil Tape
 Product Specification

Description	Product Code	Roll Size	Nominal Thickness	Rolls/Carton
Vapastop® Tape AF	780001	48mm x 45m	75 microns	24
Vapastop® Tape AF	780002	72mm x 45m	75 microns	16

Storage

Vapastop® Tape AF must be protected against damage and weather. Tape must be stored under cover in a clean, dry environment. Do not crush product.



Distributed by:
 Tasman Insulation New Zealand Limited
 9-15 Holloway Place, Penrose,
 Auckland,
 New Zealand

(1) This data sheet may have been superseded. Please refer to www.pinkbatts.co.nz for the most current information. This datasheet supersedes all previous versions. (2) Tasman Insulation New Zealand Ltd retains the right to change specifications without prior notification. (3) Do not use this product for any application not detailed in this data sheet. (4) Recommendations and advice regarding the use of this product are to be taken as a guide only. The purchaser should ascertain the suitability of this product for the particular end-use situation intended and when used in conjunction with other products. (5) Consult Tasman Insulation New Zealand Ltd for further information. (6) All claims about this product are subject to any variation caused by normal manufacturing process and tolerances. (7) The liability of Tasman Insulation New Zealand Ltd and its employees and agents for any errors or omissions in this data sheet or otherwise in relation to the product is limited to the fullest extent permitted by law. Except where the consumer acquires the goods for the purposes of a business, any rights a consumer may have under the Consumer Guarantees Act are not affected. (8) This information is provided without prejudice to Tasman Insulation New Zealand Ltd standard terms and conditions of sale.

Please consider the environment before printing this document

For further information visit www.pinkbatts.co.nz or call 0800 PINK BATTs (746 522)