

DuPont™ Flashing Tape

BUILDING SCIENCE BULLETIN



DuPont™ Flashing Tape is easy to install with a forgiving initial tack.

DuPont™ Flashing Tape provides a cost-effective way to help protect jambs, heads, corners and deep sills for today's windows and buildings.

By helping to channel water effectively outside of the home, DuPont™ Flashing Tape helps protect against water damage that can occur when moisture becomes trapped within the wall system. Providing a durable seal at the window-wall interface, DuPont™ Flashing Tape integrates easily with the complete line of DuPont™ Tyvek® Building Envelope Solutions.

DuPont™ Flashing Tape uses a superior performance butyl based adhesive system and a thermally stable polyolefin top-sheet that will not deteriorate or stain after extended exposure to temperature up to 82°C. It adheres well to most common building materials, including DuPont™ Tyvek® Building Envelope wraps, while maintaining a forgiving initial tack, thereby allowing for repositioning with its lightweight release liner and at external temperatures as low as -4°C. DuPont™ Flashing Tape meets the requirements for the AAMA 711-13 material standard at the highest classification level.

DuPont™ Flashing Tape is a premium performance, self-adhered flashing material that can be applied over a wide range of building substrates, including sheathing materials like timber, timber composite panels such as OSB and coated ply, EPS/XPS/PU foam board, fibre-cement board, concrete masonry unit (CMU) and other similar materials.

BENEFITS

- 100% butyl adhesive
- Can be installed at external temperatures as low as **-4°C**
- Excellent adhesive to most common building materials
- Meets the AAMA 711-13 material standard: Class A (no primer) and Level 3 Thermal Exposure
- **120 days** UV exposure



DuPont™ Flashing Tape comes in convenient 101mm, 152mm and 228mm x 22.9m roll and features a split release liner to help with easier product installation.



Description	Product Code	Roll size	Recommended Application
DuPont™ Flashing Tape - 101mm*	780011	101mm x 22.9m	For flashing jambs and heads of standard integral flange residential windows.
DuPont™ Flashing Tape - 152mm*	780012	152mm x 22.9m	For applications requiring better coverage on the head of the window (such as flashing onto rough-side OSB).
DuPont™ Flashing Tape - 228mm*	780013	228mm x 22.9m	

The colour PINK and Pink® are registered trademarks of Owens Corning used under license by Tasman Insulation New Zealand Ltd (Tasman). Batts® is the registered trademark of Tasman Insulation. This document supersedes all previous versions and may have been superseded; is a guide only and the purchaser should ascertain the suitability of this product for the end-use situation intended and when used in conjunction with other products; and is provided without prejudice to Tasman standard terms of sale. Tasman retains the right to change specifications without prior notice. Refer to pinkbatts.co.nz or consult Tasman for further information. Do not use this product for any application not detailed in this document. All claims about this product are subject to any variation caused by normal manufacturing process and tolerances. The liability of Tasman and its employees and agents for any errors or omissions in this document or otherwise in relation to the product is limited to the fullest extent permitted by law. Except where the consumer acquires the goods for the purposes of a business, any rights a consumer may have under the Consumer Guarantees Act are not affected.

Copyright © 2017 DuPont. The DuPont Oval Logo, DuPont™, and Tyvek® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved. K-16156 5/17