

SUREWRAP™ ROOF

SELF-SUPPORTING SYNTHETIC ROOF UNDERLAY



ROOF UNDERLAY

- BRANZ Appraised
- Fire Retardant
- Suitable for use on roof pitches of minimum 3°
- 150mm lap line printed on each edge
- No additional support required for spans below 1200mm



■ 0800 746 522

■ pinkbatts.co.nz

SUREWRAP™ ROOF

SELF-SUPPORTING SYNTHETIC ROOF UNDERLAY



Application

Sisalation® SureWrap™ Roof is a fire retardent self-supporting underlay designed for use under roof cladding. The product consists of a micro-porous water resistant film laminated between two layers of non-woven spun bonded polyolefin.

Sisalation® SureWrap™ Roof can be used within the following scope:

- The scope limitation of NZBC Acceptable Solution E2/AS1 with regards to building height and floor plan area; and,
- With masonry tile roof cladding; and,
- With metal tile and profiled metal roof cladding
- Residential and commercial applications with roof pitches of minimum 3°
- Wind Zones up to and including "Extra High"

New Zealand Building Code Requirements

Sisalation® SureWrap™ Roof is an Alternative Solution under the New Zealand Building Code: Clause E2 External Moisture

NZBC E2/AS1 Table 23		
Performance Criteria	Requirement	Performance
Absorbency	≥ 150 g/m ²	Pass
Vapour Resistance	≤ 7 MNs/g	Pass
Water Resistance	≥ 100mm	Pass
pH of Extract	≥ 5.5 and ≤ 8.0	Pass
Shrinkage	≤ 0.5%	0%
Mechanical	Tensile Strength (Average)	MD=3.94 kN/m, CD=3.66 kN/m
	Edge Tear (Average)	MD=204 N, CD=191N
Additional Information		
Flammability Index	Fire Retardent ≤ 5	
Wind Load Zone	Up to and including Extra High	

Product Specifications

Description	Product Code	Roll Size	Area	GSM
Sisalation® SureWrap™ Roof	799400	1250mm x 40.0m	50m ²	172gsm

Sisalation® SureWrap™ has been assessed by BRANZ for both commercial and residential applications. For information and product data sheets visit pinkbatts.co.nz or call 0800 746 522



Distributed by:

Tasman Insulation New Zealand Limited
9-15 Holloway Place, Penrose,
Auckland 1061,
New Zealand

(1) This document may have been superseded. Please refer to www.pinkbatts.co.nz for the most current information. This document supersedes all previous versions. (2) Tasman Insulation New Zealand Ltd retains the right to change specifications without prior notification. (3) Do not use this product for any application not detailed in the relevant data sheet. (4) Recommendations and advice regarding the use of this product are to be taken as a guide only. The purchaser should ascertain the suitability of this product for the particular end-use situation intended and when used in conjunction with other products. (5) Consult Tasman Insulation New Zealand Ltd for further information. (6) All claims about these products are subject to any variation caused by normal manufacturing process and tolerances. (7) The liability of Tasman Insulation New Zealand Ltd and its employees and agents for any errors or omissions in this document or otherwise in relation to the product is limited to the fullest extent permitted by law. Except where the consumer acquires the goods for the purposes of a business, any rights a consumer may have under the Consumer Guarantees Act are not affected. (8) This information is provided without prejudice to Tasman Insulation New Zealand Ltd standard terms and conditions of sale.